



THE NUT PLACE

6605 N. Gessner Houston, TX 77040-4015

Ph: 713-462-3147

sales@thenutplace.com


www.thenutplace.com

STOVER C LOCK NUT

AVAILABLE TYPES

ALL METAL HEX LOCKNUTS GRADE C MED. CARBON ZINC & WAX CR+3

Call or email us if you're looking for other diameters.



DIAMETERS

THREAD COURSE	THREAD FINE	METRIC (COURSE, ZP)
1/4 -20	1/4 -28	5mm
5/16 -18	5/16 -24	6mm
3/8 -16	3/8 -24	8mm
7/16 -14	7/16 -20	10mm
1/2 -13	1/2 -20	12mm
9/16 -12	9/16 -18	14mm
5/8 -11	5/8 -18	16mm
3/4 -10	3/4 -16	18mm
7/8 -9	7/8 -14	20mm
1 -8	1 -14	22mm
1 1/8 -7	1 1/8 -12	24mm
1 1/4 -7	1 1/4 -12	27mm
1 3/8 -6	1 1/2 -12	
1 1/2 -6		
1 3/4 -5		
2 -4 1/2		

Fastener Finishes

Nuts are available with different finishes like zinc, galvanized, xylan, cad or just plain black. If you need to be supplied with another finish, then call or email us. We can provide finishes to your specification.

Technical Data

NUT/BOLT COMPATIBILITY

For a Grade C locknut, the specified minimum ultimate tensile strength of the bolt is not less than 105 nor greater than 150 (ksi).

MECHANICAL PROPERTY REQUIREMENTS

For a Grade C locknut from 1/4" through 1 1/2", the proof load stress is 150,000 (psi).